

| QUICK GUIDE | DEVICE INFORMATION | SETUP DIAGRAM | REMOTE CONTROL | REMOTE CONTROL |
|--|---|-------------------|---|--|
| <p>1 Dongle 2 Quick Guide 3 Remote Control 4 Power Adapter 5 Battery 6 USB Cable</p> | <p>1 LAN 2 RESET 3 Micro USB 4 HDMI 5 USB-C</p> | <p>ISP Router</p> | <p>Do more on your TV with your voice</p> <p>Your TV is more helpful than ever. Ask Google to find movies, stream apps, play music, and control the TV - all with your voice. Even get answers, control smart home devices, and more. Press the Google Assistant button on the remote to get started.</p> <p>Hey Google</p> | <p>Pairing guide</p> <p>Long press the Back and Home button at the same time until the red light flashes quickly, then release. This means the remote control has entered pairing mode. Wait for a few seconds without pressing any buttons until a message pops up on the screen that the remote has paired successfully.</p> |

| SETUP | SPECIFICATION | SAFETY INFORMATION | DECLARATION | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|--------------------|-------------|---------|----------------|-----|---------|-------|----------|-------|--|----------------|--|-------------------|--|--------------|-------------------|--------------|-------------------|-------|--|----------------|-------|-------------------|------------|---|---|
| <p>Complete the on-screen setup</p> <p>Follow the on-screen instructions using your remote to navigate through the setup process.</p> | <table border="1"> <thead> <tr> <th colspan="2">Hardware</th> </tr> </thead> <tbody> <tr> <td>Chipset</td> <td>Amlogic S905Y4</td> </tr> <tr> <td>RAM</td> <td>2GB DDR</td> </tr> <tr> <td>Flash</td> <td>eMMC 8GB</td> </tr> <tr> <th colspan="2">Video</th> </tr> <tr> <td>Video Decoding</td> <td>AV1 MP-10@L5.1 up to 4Kx2K@60fps VP9 Profile-2 up to 4Kx2K@60fps H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps AVS2-P2 Profile up to 4Kx2K@60fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 MVC up to 1080P@60fps MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) WMV/JVC-1 SP/MP/AP up to 1080P@60fps AVS-P16(AVS+) /AVS-P2 Jizhun Profile up to 1080P@60fps MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) RealVideo 8/9/10 up to 1080P@60fps</td> </tr> <tr> <td>Video File Format</td> <td>Support *.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm, *.jpg, *.bmp, *.gif etc...</td> </tr> <tr> <td>Video Output</td> <td>HDMI 2.1, HDCP2.2</td> </tr> <tr> <td>Aspect Ratio</td> <td>Auto, Full screen</td> </tr> <tr> <th colspan="2">Power</th> </tr> <tr> <td>DC Input Range</td> <td>5V 1A</td> </tr> <tr> <td>Power Consumption</td> <td>Maximum 5W</td> </tr> </tbody> </table> | Hardware | | Chipset | Amlogic S905Y4 | RAM | 2GB DDR | Flash | eMMC 8GB | Video | | Video Decoding | AV1 MP-10@L5.1 up to 4Kx2K@60fps VP9 Profile-2 up to 4Kx2K@60fps H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps AVS2-P2 Profile up to 4Kx2K@60fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 MVC up to 1080P@60fps MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) WMV/JVC-1 SP/MP/AP up to 1080P@60fps AVS-P16(AVS+) /AVS-P2 Jizhun Profile up to 1080P@60fps MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) RealVideo 8/9/10 up to 1080P@60fps | Video File Format | Support *.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm, *.jpg, *.bmp, *.gif etc... | Video Output | HDMI 2.1, HDCP2.2 | Aspect Ratio | Auto, Full screen | Power | | DC Input Range | 5V 1A | Power Consumption | Maximum 5W | <p>CAUTION!</p> <p>NOTICE: To prevent fire and electric shock, do not expose this device to rain or moisture. In order to avoid any possible risk of electric shock, never attempt to open the unit. In case of the unit breaking down, repair of the unit should be carried out by qualified technicians. No part of this unit should be repaired by users.</p> <p>WARNING!</p> <ul style="list-style-type: none"> Place the device in a well-ventilated location to prevent accumulation of internal heat. Protect the device from high temperatures, humidity, water and dust. Do not place any objects that might damage your unit near it (e.g. liquid filled objects or candles). | <p>Google TV is the name of this device's software experience and a trademark of Google LLC. Google and YouTube are trademarks of Google LLC. Google Assistant is not available in certain languages and countries. Availability of services varies by country and language.</p> <p>The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.</p> |
| Hardware | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Chipset | Amlogic S905Y4 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RAM | 2GB DDR | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Flash | eMMC 8GB | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video Decoding | AV1 MP-10@L5.1 up to 4Kx2K@60fps VP9 Profile-2 up to 4Kx2K@60fps H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps AVS2-P2 Profile up to 4Kx2K@60fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 MVC up to 1080P@60fps MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) WMV/JVC-1 SP/MP/AP up to 1080P@60fps AVS-P16(AVS+) /AVS-P2 Jizhun Profile up to 1080P@60fps MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) RealVideo 8/9/10 up to 1080P@60fps | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video File Format | Support *.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm, *.jpg, *.bmp, *.gif etc... | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video Output | HDMI 2.1, HDCP2.2 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Aspect Ratio | Auto, Full screen | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DC Input Range | 5V 1A | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power Consumption | Maximum 5W | | | | | | | | | | | | | | | | | | | | | | | | | | |



- 2.产品不能变形、压痕、划伤、脏污等缺陷
- 3.图案文字印刷清晰，色差在允许范围内
- 4.风琴折
- 5.80g书纸，4C

| | | | |
|-----------|-------|-------|---------------------------------|
| 未注尺寸公差 | 市场部审核 | 单位 | mm |
| 0<L≤200 | 1mm | 软件部审核 | 型号 |
| 200<L≤400 | 2mm | 质量部审核 | 图号 SY.SMS.B7.GZ2212038 |
| | 审批 | 物料编号 | 3301-ML0386-PP0A |
| | | | 深圳感臻科技有限公司 |
| | | | Shenzhen SEI Robotics Co., Ltd. |